

DIMENSIONS



SUMMARY

CAPACITY

2HP

DIMENSIONS NET W X H X D (MM) INDOOR / OUTDOOR

998 x 345 x 210

770 x 545 x 288

MAIN TECHNOLOGY

Dual Inverter

ADDITIONAL BENEFIT

Active Energy Control

CAPACITY

Cooling (Min ~ Rated ~ Max)	5.28 kW 18,000 Btu/h 18,990 kJ/h
------------------------------------	--

Capacity	2.0HP
-----------------	-------

POWER INPUT

Cooling (Min ~ Rated ~ Max)	1,540 W
------------------------------------	---------

RUNNING CURRENT

Cooling (Min ~ Rated ~ Max)	7.10 A
------------------------------------	--------

EER

EER	3.43 W/W 11.69 (Btu/h)/W 12.33 (kJ/h)/W
------------	---

POWER SUPPLY

Power Supply	1, 230, 60 (Ø, V, Hz)
---------------------	-----------------------

Available Voltage Range	187 ~ 276 V
--------------------------------	-------------

Power Factor - Cooling	94%
-------------------------------	-----

Moisture Removal	1.25 l/h 2.64 pts/h
-------------------------	------------------------

Circuit Breaker	25 A
------------------------	------

Power Supply Cable	3 × 1.5 No. × mm ²
---------------------------	-------------------------------

Power Supply to Unit	Indoor
-----------------------------	--------

Power and Communication Cable	4 × 1.5 No. × mm ²
--------------------------------------	-------------------------------

INDOOR UNIT

Air Flow Rate - Cooling, Max/H/M/L 18/12.7/10.2/8.4 m³/min
635.7/448.5/360.2/296.6 CFM

Fan Motor Speed - Cooling, Max/H/HM/M/ML/L/SL 1500/1150/1050/950/860/770/700 rpm

Sound Pressure Level - Cooling, Max/H/M/L/SL -/45/40/37/32 dB(A)

Dimensions (W × H × D) - Net 998 x 345 x 210 mm

Dimensions (W × H × D) - Shipping 1068 x 425 x 279 mm

Weight - Net 11.2kg

Weight - Shipping 13.2kg

Disconnect Switch 25 A

Exterior Color Code Munsell 7.5BG 10/2 (RAL 9016)

Operation Range - Cooling 16 ~ 32 °C DB
61 ~ 90 °F DB
10 ~ 23 °C WB
50 ~ 73.4 °F WB

OUTDOOR UNIT

Air Flow Rate - Max 31.0 m³/min
1095 CFM

Sound Pressure Level - Cooling, Rated 53 dB(A)

Dimensions (W × H × D) - Net 770 x 545 x 288 mm

Dimensions (W × H × D) - Shipping 920 x 588 x 393 mm

Weight - Net 32.5kg

Weight - Shipping	34.8kg
Max. Fuse Size	15 A
Exterior Color Code	Munsell 9.54Y 8.34/1.31 (RAL 9001)
Operation Range - Cooling	18 ~ 48 °C DB

PIPING

Size - Liquid	ø 6.35 mm
Size - Gas	ø 12.7 mm
Connections Method - Indoor/Outdoor	Flared/Flared
Drain Hose Size - O.D, I.D	21.5, 16.0 mm
Max Piping Length Capacity	98.7%

BETWEEN INDOOR & OUTDOOR

Piping Length - Min/Standard/Max	3/7.5/30 m
Piping Length - No Charge	12.5 m
Max. Elevation Difference	20m
Piping Connection Heat Insulation	Both liquid and gas pipes

REFRIGERANT

Type	R32
Pre Charge	950g
Additional Charge	15g/m

Control	Capillary
---------	-----------

Global Warning Potential	675
--------------------------	-----

t-CO ₂ eq	0.641
----------------------	-------

TOOL CODE(CHASSIS)

Indoor / Outdoor	SK / UL2
------------------	----------

COMPRESSOR

Type	Twin Rotary
------	-------------

Model	DAT156MAD
-------	-----------

Motor Type	BLDC
------------	------

Oil Type / Maker	PVE (FW68D) / IDEMITSU
------------------	------------------------

Oil Charge	400cc
------------	-------

Manufacturer / Country of Origin	LG Electronics / China
----------------------------------	------------------------

FAN(INDOOR)

Type	Cross Flow Fan
------	----------------

Motor Output	30W
--------------	-----

FAN(OUTDOOR)

Type	Propeller Fan
------	---------------

Motor Type	BLDC
------------	------

Motor Output	43W
--------------	-----

Motor Insulation	Class E
-------------------------	---------

Motor Enclosure / Ingress Protection	TEAO/IPX4
---	-----------

HEAT EXCHANGER

Evaporator - Material, Tube / Fin	Cu/Al
--	-------

Evaporator - (\emptyset x Row x Column x FPI x L) x Qty.	($\emptyset 7 \times 2 \times 16 \times 20 \times 744$) x 1
--	---

Evaporator - Corrosion Protection	PCM
--	-----

Evaporator - Fin Type	Slit
------------------------------	------

Condenser - Material, Tube / Fin	Cu/Al
---	-------

Condenser - (\emptyset x Row x Column x FPI x L) x Qty.	($\emptyset 7 \times 2 \times 24 \times 18 \times 823$) x 1
---	---

Condenser - Corrosion Protection	Gold
---	------

Condenser - Fin Type	Louver
-----------------------------	--------
