


DIMENSIONS



SUMMARY

CAPACITY

2.5HP

DIMENSIONS NET W X H X D (MM) INDOOR / OUTDOOR

998 x 345 x 210

870 x 650 x 330

MAIN TECHNOLOGY

Dual Inverter

ADDITIONAL BENEFIT

Active Energy Control

CAPACITY

Cooling (Min ~ Rated ~ Max)	6.30 kW 21,500 Btu/h 22,683 kJ/h
------------------------------------	--

Capacity	2.5HP
-----------------	-------

POWER INPUT

Cooling (Min ~ Rated ~ Max)	1,850 W
------------------------------------	---------

RUNNING CURRENT

Cooling (Min ~ Rated ~ Max)	8.50 A
------------------------------------	--------

EER

EER	3.41 W/W 11.62 (Btu/h)/W 12.26 (kJ/h)/W
------------	---

POWER SUPPLY

Power Supply	1, 230, 60 (Ø, V, Hz)
---------------------	-----------------------

Available Voltage Range	187 ~ 276 V
--------------------------------	-------------

Power Factor - Cooling	97.2%
-------------------------------	-------

Moisture Removal	2.80 l/h 5.92 pts/h
-------------------------	------------------------

Circuit Breaker	30 A
------------------------	------

Power Supply Cable	3 × 1.5 No. × mm ²
---------------------------	-------------------------------

Power Supply to Unit	Indoor
-----------------------------	--------

Power and Communication Cable	4 × 1.5 No. × mm ²
--------------------------------------	-------------------------------

INDOOR UNIT

Air Flow Rate - Cooling, Max/H/M/L	20/15/12.5/10.6 m ³ /min 706/530/441.5/374 CFM
---	--

Fan Motor Speed - Cooling, Max/H/HM/M/ML/L/SL	1600/1200/1100/1000/920/850/700 rpm
--	-------------------------------------

Sound Pressure Level - Cooling, Max/H/M/L/SL	-/47/41/37/32 dB(A)
---	---------------------

Dimensions (W × H × D) - Net	998 × 345 × 210 mm
-------------------------------------	--------------------

Dimensions (W × H × D) - Shipping	1068 × 425 × 279 mm
--	---------------------

Weight - Net	11.6kg
---------------------	--------

Weight - Shipping	13.4kg
--------------------------	--------

Disconnect Switch	30 A
--------------------------	------

Exterior Color Code	Munsell 7.5BG 10/2 (RAL 9016)
----------------------------	-------------------------------

Operation Range - Cooling	16 ~ 32 °C DB 61 ~ 90 °F DB 10 ~ 23 °C WB 50 ~ 73.4 °F WB
----------------------------------	--

OUTDOOR UNIT

Air Flow Rate - Max	49.0 m ³ /min 1730 CFM
----------------------------	--------------------------------------

Sound Pressure Level - Cooling, Rated	55 dB(A)
--	----------

Dimensions (W × H × D) - Net	870 × 650 × 330 mm
-------------------------------------	--------------------

Dimensions (W × H × D) - Shipping	1040 x 710 x 455 mm
--	---------------------

Weight - Net	42.5kg
---------------------	--------

Weight - Shipping	45.9kg
--------------------------	--------

Max. Fuse Size	20A
-----------------------	-----

Exterior Color Code	Munsell 9.54Y 8.34/1.31 (RAL 9001)
----------------------------	------------------------------------

Operation Range - Cooling	18 ~ 48 °C DB
----------------------------------	---------------

PIPING

Size - Liquid	ø 6.35 mm
----------------------	-----------

Size - Gas	ø 15.88 mm
-------------------	------------

Connections Method - Indoor/Outdoor	Flared/Flared
--	---------------

Drain Hose Size - O.D, I.D	21.5, 16.0 mm
-----------------------------------	---------------

Max Piping Length Capacity	94.8%
-----------------------------------	-------

BETWEEN INDOOR & OUTDOOR

Piping Length - Min/Standard/Max	3/7.5/30 m
---	------------

Piping Length - No Charge	12.5 m
----------------------------------	--------

Max. Elevation Difference	20m
----------------------------------	-----

Piping Connection Heat Insulation	Both liquid and gas pipes
--	---------------------------

REFRIGERANT

Type	R32
-------------	-----

Pre Charge	1150g
Additional Charge	20g/m
Control	Electronic Expansion Valve
Global Warning Potential	675
t-CO ₂ eq	0.776

TOOL CODE(CHASSIS)

Indoor / Outdoor	SK / U24A
------------------	-----------

COMPRESSOR

Type	Twin Rotary
Model	DAT156MAD
Motor Type	BLDC
Oil Type / Maker	PVE (FW68D) / IDEMITSU
Oil Charge	400cc
Manufacturer / Country of Origin	LG Electronics / China

FAN(INDOOR)

Type	Cross Flow Fan
Motor Output	30W

FAN(OUTDOOR)

Type	Propeller Fan
------	---------------

Motor Type	BLDC
-------------------	------

Motor Output	85W
---------------------	-----

Motor Insulation	Class E
-------------------------	---------

Motor Enclosure / Ingress Protection	TEAO/IPX4
---	-----------

HEAT EXCHANGER

Evaporator - Material, Tube / Fin	Cu/Al
--	-------

Evaporator - (\varnothing x Row x Column x FPI x L) x Qty.	($\varnothing 7 \times 2 \times 16 \times 20 \times 744$) x 1
--	---

Evaporator - Corrosion Protection	PCM
--	-----

Evaporator - Fin Type	Slit
------------------------------	------

Condenser - Material, Tube / Fin	Cu/Al
---	-------

Condenser - (\varnothing x Row x Column x FPI x L) x Qty.	($\varnothing 7 \times 2 \times 28 \times 18 \times 940$) x 1
---	---

Condenser - Corrosion Protection	Gold
---	------

Condenser - Fin Type	Louver
-----------------------------	--------
